

CONTINUATION REPORT

ICN 941989RF03	KO M01	MATL ITEM ID 00379
-------------------	-----------	-----------------------

REQ DOC NO. N42158-4310V153	REV	CONTRACT NO.	REFERENCE DOC NO.	ATTACHMENT (c)
--------------------------------	-----	--------------	-------------------	-------------------

NAME OF OFFEROR OR CONTRACTOR

ITEM NO.	SUPPLIES/SERVICES	QTY	UNIT	UNIT PRICE	AMOUNT
0001	<p>9B 3950 LLR140278</p> <p>CHAIN HOIST</p> <p>HOOK TYPE MANUAL CHAIN HOIST SPUR GEARED, HOOK SUSPENSION 5 TON (10000 LB) CAPACITY CHESTER ZEPHYR 130-5 WITH 20 FT OF LIFT, 20 FT OF HAND CHAIN</p> <p>HOISTS SHALL MEET THE REQUIREMENTS OF ATTACHMENT (1)</p> <p>CERTIFICATE OF COMPLIANCE REQUIRED (SEE ATTACHMENT 2)</p>	4	EA		
	ACR:				

ATTACH (C1)

Attachment (1)
Chain Hoist Ordering Specifications for Attach (C)
Document Number 4310V153

Ordering Specifications – 5 Ton Chain Hoist
5-ton capacity Chester Zephyr Hook Type Hoist
Part # 130-5 (or 130-0500DOD)

Quantity – 4

1. Manufactured in accordance with ASME B30.16 and conforming to performance standards of ASME HST-2.
2. 20 ft. of lift.
3. 20 ft. of hand chain drop.
4. No cast iron load bearing components.
5. No plating of any components.
6. The hoist shall be capable of withstanding static and dynamic load tests at 125% (+5%, -0%) of the manufacturer's rated safe working load for a period of ten (10) minutes minimum.
7. The hoist shall have a minimum breaking strength that is 4 times the manufacturer's rated safe working load.
8. The hooks shall be weldless and forged, and shall have a minimum breaking strength that is 4 times the manufacturer's rated safe working load. NDT of hooks is not required.
9. The hooks shall be removable and have a swivel capacity.
10. No part of the chain hoist body or hooks shall contain paint.
11. The vendor shall provide a Certificate of Compliance that verifies the hand chain hoists per this order meet the above requirements. Failure to provide this Certificate of Compliance shall be cause for rejection of the material.
12. All above required information shall be traceable to the hand chain hoists received per this order. Documentation shall be traceable to the purchase contract under which the material is provided.

