

## CESE and CEEI Painting Requirements

- Painting Requirements: The Contractor shall comply with NAVFAC P-300, Section 2 for painting requirements. Units shall be spot painted the same color as the main body of the unit to provide corrosion control. The Contractor shall not paint the entire unit unless directed in the individual task order. Spot painting costs or a recommendation to paint the entire unit shall be included in the Contractor's cost estimate. Surfaces to be painted shall be cleaned and dried to ensure that they are free from contaminants such as oil, grease, welding slag and other interfering substance. Immediately after cleaning and before any corrosion product or other coating interfering matter can develop, the surface shall be prepared or created to ensure the adhesion of the coating system. The painting shall consist of at least one coat of primer and one finish coat. The primer shall be applied to a clean, dry surface as soon as possible after cleaning and treating and be compatible with the top coat. The Base Coat will be a minimum of 4 Mils thick Epoxy Primer. The Finish Coat will be a minimum of 4 Mils thick Polyurethane. The Paint Codes are from 595 Mil. Spec. Fan Deck Color Chart. 1.) Code # 34064, Olive Drab (O.D.) Green-Flat, Low Luster, Polyurethane 2.) Code # 33303, Tan, Flat, Low Luster, Polyurethane.
- Prior to primer and paint application, all devices and components shall be masked off. The contractor shall paint all interior and exterior surfaces, doorjambes, coverjambes, and interior side of doors and covers.
- All Military Tactical Equipment shall be painted with CARC Paint.