

KEE JMLS
L0173-6450
L0140-6458
THRU
L0140 - L0461

SPECIFICATIONS FOR WELDING TABLE:

DEMENSIONS: 4m x 2m x 2m

TABLETOP: 24.5-27mm material thickness; surface hardness approx. 750; borehole spacing 100mm with additional 100 mm grid offset by 50mm in the x and y axis, aka diagonal grid; side panel 200mm high;

TABLE LEGS: Height can adjust from 450mm to 700mm; load capacity 2,000kg

MATERIAL: High quality steel

Shipping Bracket with Fastening Plate- 1800 kg load carrying capacity, 150mm L x 150mm W x 25mm H

ACCESSORIES:

Tool set-including the following:

- *14(ea) **Screw Clamp Standard**-vertical height 310mm; horizontal length 200mm, 40 - 165 Clamping Range
- *10(ea) **Screw Clamp Standard 45/90**- vertical height 310mm; 170mm Spindle Length
- *8(ea) **Prism Ø 50 135° with screwed-in collar**; M16 hole mount, 20mm H, 50mm dia.
- *36(ea) **Fast Clamping Bolt, Short**- 95mm L, 28mm dia
- *8(ea) **Magnetic clamping bolt**; 68mm L. 34mm dia.
- *12(ea) **Universal Stop 150 L, nitrided**- 150mm L x 50mm W x 25mm T, 100mm slot length
- *12(ea) **Universal Stop 225 L, nitrided**- 225mm L x 50mm W x 25mm T, 100mm slot length
- *4(ea) **Universal Stop 500 S**- 500mm L x 50mm W x 25mm T, 200mm slot length
- *12(ea) **Stop and Clamping Square 175 L nitrided** – 175mm L x 50mm W x 175mm H x 25mm T
- *2(ea) **Stop and Clamping Square 500 G**- 200mm L x 75mm W x 500mm H x approx 27mm T
- *1(ea) **L&R Stop and Clamping Square 500 G**- 276mm L x 95mm W x 500mm H x approx 27mm T
- *1(ea) **L&R Stop and Clamping Square 750 GK**- 276mm L x 85mm W x 750mm H x approx 27mm T
- *1(ea) **L&R Stop and Clamping Square 800 GK nitride**- 376mm L x 95mm W x 800 H x approx. 27mm T
- *1(ea) **Tool Trolley**- 660mm L x 900mm W x 1040mm H

Clamping Plate 400 - 600 LBS for ASME/ANSI flanges- 350mm L x 250mm W x 25mm T; Nitrided; ANSI/ASME B 16.5 300lbs from ½" to 8"

Riser Block- 2000mm x 200mm x W x 200mm H

Universal Bolt, Long -125mm L x 28mm dia

Corner Connection- 200mm L x 150mm W x 120mm H

Sliding Base- 350mm L x 300mm W x 50mm T

Flat Clamping Bolt, Short- 75mm L x 28mm dia

Eccentric Stop 100- Diameter: 100mm x 25mm T

Clamping Plate 400 - 600 LBS for ASME/ANSI flanges- 350mm L x 250mm W x 25mm T

Prism Collar Screw with countersunk bolt- 27mm x 28mm