

Specification:

Model: FE13

Extinguisher Part No: 429022

Agent Capacity: 13.25 lb. (6 kg)

UL/ULC Rating: 2-A: 10-B:C (Class A Fires)

USCG Classification (Marine): Type B:C, Size 1

Approvals: UL/ULC/FAA/USCG

Operating Temperature Range: -40 degrees Fahrenheit to 120 degrees Fahrenheit (-40 degrees Celsius to 49 degrees Celsius)

Maximum Effective Range: 14-16 ft. (4.3-4.9m)

Charged Weight (with agent): 25.63 lb. (11.63 kg)

Discharge Time (sec): 13.5

Agent Flow Rate: 1.12 lb/sec (.14 kg/sec.)

Dimensions: Height: 22-1/2 in. (572 mm) Width: 9-1/2 in. (241 mm) Depth: 7 in. (178 mm)

Fire suppression Capability: Novice: 10 sq ft., Experienced: 25 sq. ft.

Extinguishing Agent: FE-36, HALON 1211, HALOTRON I

Agent: FE-36™ is a colorless, odorless, electrically non-conductive "clean" agent which discharges as a liquid and flashes to a gas, providing an increased effective firefighting range. FE-36 will not cause thermal shock damage to delicate electronic equipment. FE-36 has been accepted by the EPA for commercial, industrial, and military use under the EPA's SNAP program.